

Kleen-Plus[®]

DEMINERALISING SYSTEMS

When High purity deionised water is required ,the most convenient choice is APL's exchange DI service. Using APL's DI service means that pure water is only a phone call away



NO CAPITAL INVESTMENT

Systems are provided on an exchange basis

NO REGENERATION

Since the DI tanks are regenerated off-site there is no regeneration labour, no chemicals to purchase and handle and no wastes to be neutralised and discharged.

DEPENDABILITY

When tanks are exhausted APL will regenerate a new one for you and arrange delivery direct to your door.

PART #	TANK SIZE	PORTS	FLOW LPM	CAPACITY (Litres) *
MB618N	6 x 18	1"	5	1500
MB735N	7 x 35	1"	10	4500
MB744N	7 x 44	1"	20	7500
MB948N	9 x 48	1"	30	12000
MB1054N	10 x 54	1"	40	15000
MB1252N	12 x 52	1"	50	22500

* MULTIPLY THIS CAPACITY BY CORRECTION FACTOR BELOW FOR TDS READINGS OTHER THAN 100

TDS	25	50	75	100	200	300	400	500	600
FACTOR	4	2	1.3	1	0.5	0.33	0.25	0.2	0.17

OPTIONAL EXTRAS

Indicator light which indicates when resin has expired

1 microseimen indicator light	28/CE
5 microseimen indicator light	28/CD

FEATURES AND BENEFITS

- Simple to install
- 5 sizes for greater choice
- Low cost tank exchange system
 - No electricity
 - No waste water
- Nuclear grade mixed bed resins
- Optional expended resin indicator light

Max. Temperature 50°
Max Pressure 100 PSI

Larger units and auto regeneration systems also available